


7.10 Type: RSY



單位：mm

型號	規格													
	d	l	Da	D	L	B	X	Y	Z	Q	L1	n	(Ca Kgf)	(Coa Kgf)
1202-3	12	2	1.2	24	30	9	3	1.5	12	Ø3	4	T3	265	377
1204-3	12	4	2.381	24	35	11.5	3	1.5	12	Ø3	5	T3	645	693
1205-3	12	5	2	24	40	14	3	1.5	12	Ø3	5	T3	514	594
1210-2	12	10	2	24	40	14	3	1.5	12	Ø3	5	T2	390	466
1602-3	16	2	1.2	28	40	10	5	2	20	Ø3	5	T3	300	503
1604-4	16	4	2.381	28	45	12.5	5	2	20	Ø3	7	T4	944	1254
1605-3	16	5	3.175	28	45	12.5	5	2	20	Ø3	7	T3	1049	1144
★ 1605-4	16	5	3.175	28	50	15	5	2	20	Ø3	7	T4	1344	1525
1610-3	16	10	3.175	28	45	12.5	5	2	20	Ø3	7	T3	1181	1496
1616-2	16	16	3.175	28	45	12.5	5	2	20	Ø3	7	T2	833	997
2005-3	20	5	3.175	36	47	13.5	5	2	20	Ø3	7	T3	1181	1496
★ 2005-4	20	5	3.175	36	53	16.5	5	2	20	Ø3	7	T4	1512	1995
2006-3	20	6	3.969	36	53	16.5	5	2	20	Ø3	7	T3	1568	1787
2010-3	20	10	3.969	36	68	24	5	2	20	Ø3	7	T3	1621	1925
2020-4	20	20	3.175	36	55	17.5	5	2	20	Ø3	7	T4	1659	2464
★ 2505-4	25	5	3.175	40	53	16.5	5	2	20	Ø3	7	T4	1704	2581
▲ 2510-3	25	10	3.5	40	54	17	5	2	20	Ø3	7	T3	1614	2460
★ 3205-4	32	5	3.175	50	53	11.5	6	2.5	30	Ø3	7	T4	1924	3403
3210-3	32	10	6.35	50	70	20	6	2.5	30	Ø3	7	T3	3775	5877
3220-3	32	20	3.969	50	78	24	6	2.5	30	Ø3	7	T3	2141	3576
★ 4005-4	40	5	3.175	63	56	13	6	2.5	30	Ø3	7	T4	2142	4342
4010-3	40	10	6.35	63	80	25	6	2.5	30	Ø3	7	T3	4216	7556
4020-3	40	20	5.556	63	83	26.5	6	2.5	30	Ø3	7	T3	3782	6468
5010-3	50	10	6.35	75	82	23	6	2.5	36	Ø3	7	T3	4633	9235
6310-4	63	10	6.35	85	90	29	6	3.5	32	Ø5	14	T4	6700	16230

★ 可生產左牙

▲ 珠徑3.5mm,請另選購3.5珠徑之螺桿搭配